

AXIS M1124-E Network Video Camera

Outdoor, affordable and feature-rich with HDTV 720p

AXIS M1124-E is an outdoor-ready day and night camera delivering HDTV 720p video in up to 25/30 frames per second. The camera is fitted with an IR-corrected, varifocal and easily exchangeable CS-mount lens with DC-iris. AXIS M1124-E includes Axis' Zipstream technology that significantly reduces bandwidth and storage requirements. The camera supports WDR - Forensic Capture, providing video optimized for forensic purposes in scenes with complex light conditions. The lightweight IP66- and IK10-rated camera supports Power over Ethernet to simplify installation, microSD card slot for edge storage, digital input and output ports for connection with external equipment.

- > **Outdoor-ready**
- > **HDTV 720p in up to 25/30 fps**
- > **Varifocal CS-mount lens**
- > **WDR - Forensic Capture**
- > **Axis' Zipstream technology**



AXIS M1124-E Network Video Camera

Camera		Built-in installation aids	Pixel counter
Image sensor	Progressive scan RGB CMOS 1/3"	General	
Lens	Varifocal, IR corrected, CS-mount, DC-iris, 3-10.5 mm Horizontal field of view: 91°-32° Vertical field of view: 49°-18°	Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B
Day and night	Automatically removable infrared-cut filter	Sustainability	PVC free PCB is bromine-free
Minimum illumination	Color: 0.25 lux F1.4 B/W: 0.05 lux F1.4	Memory	512 MB RAM, 256 MB Flash
Shutter time	1/66500 to 1 s	Power	8-28 V DC or Power over Ethernet (PoE) IEEE 802.3af Class 2, max 5.0 W, typical 3.6 W
Video		Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for one input and one output (12 V DC output, max. load 15 mA) DC input, terminal block
Video compression	H.264 Baseline, Main and High profile (MPEG-4 Part 10/AVC) Motion JPEG	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Resolutions	1280x720 to 160x90	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10-100% RH (condensing)
Frame rate	Up to 25/30 fps in all resolutions	Storage conditions	-20 °C to 50 °C (-4 °F to 122 °F)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis' Zipstream technology in H.264 Controllable frame rate and bandwidth, VBR/MBR H.264	Approvals	EN 55022 Class A, EN 61000-6-1, EN 61000-3-2, EN 61000-3-3, EN 61000-6-2, EN 55024, EN 50121-4, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class A, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-78 IEC/EN/UL 60950-22, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10, IEC 60721-4-4 Class 4M4
Image settings	WDR - forensic capture: up to 120 dB depending on scene, manual shutter time, compression, color, brightness, sharpness, contrast, white balance, exposure control (including automatic gain control), exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270°, aspect ratio correction, text and image overlay, privacy mask, mirroring of images	Dimensions	222 x 137 x 448 mm (8 3/4 x 5 3/8 x 17 5/8 in) including wall mount
Pan/Tilt/Zoom	Digital PTZ	Weight	1.6 kg (3.5 lb) including wall mount
Network		Included accessories	AXIS T94Q01A Wall Mount, Resistorx T20 tool, Connector kit, Installation Guide, Windows decoder 1-user license
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Optional accessories	AXIS T94R01P Conduit Back Box, AXIS T98A16-VE Surveillance Cabinet Series, AXIS T91A47 Pole Mount, AXIS T90B Illuminators
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
System integration		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection. ONVIF [®] Profiles S and G, specifications at www.onvif.org	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross-line detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
Event triggers	Analytics, edge storage events, external input	Environmental responsibility: www.axis.com/environmental-responsibility	
Event actions	File upload via FTP, HTTP, HTTPS, SFTP, network share and email Notification via email, HTTP, HTTPS, TCP Video recording to edge storage, pre- and post-alarm video buffering, PTZ preset, guard tour, send video clip, send SNMP trap, day/night vision mode, WDR mode, status LED indicator, output port		
Data streaming	Event data		