

WiFi USB Adapter



WiFi USB adapter with a mini USB converter

Introduction

The WiFi USB Adaptor is designed to connect the GV IP devices to the wireless network. This product complies with IEEE 802.11 b/g/n (Draft 3.0) standards for wireless networking. The WiFi USB Adaptor is a plug-and-play device; you don't need to install any driver for the device to work.

Compatible GV IP Devices

The WiFi USB Adaptor is compatible with the following hardware and firmware.

GV-Video Server

- ⊙ GV-VS04H, GV-VS04A (firmware V1.05 and later)
- ⊙ GV-VS12 (firmware V1.05 and later)
- ⊙ GV-VS11 (firmware V1.0 and later)

GV-Compact DVR

- ⊙ GV-Compact DVR V2 (firmware V1.07 and later)
- ⊙ GV-Compact DVR V3 4-CH (firmware V1.01 and later)
- ⊙ GV-Compact DVR V3 8-CH (firmware V1.0 and later)

GV-IP Cameras

- ⊙ GV-BX1200 Series (firmware V1.15 and later)
- ⊙ GV-BX1300 Series (firmware V1.15 and later)
- ⊙ GV-BX2400 Series (firmware V1.15 and later)
- ⊙ GV-BX3400 Series (firmware V1.15 and later)
- ⊙ GV-BX5300 Series (firmware V1.15 and later)
- ⊙ GV-MFD1501 Series (firmware V2.08 and later)
- ⊙ GV-MFD2401 Series (firmware V2.09 and later)
- ⊙ GV-MFD2501 Series (firmware V2.11 and later)
- ⊙ GV-MFD3401 Series (firmware V2.09 and later)
- ⊙ GV-MFD5301 Series (firmware V2.09 and later)

PN300, SQP133 (firmware V1.01 and later)

GV-IP Decoder Box, GV-Pad (firmware V1.02 and later)

Specifications

Network Standard	IEEE 802.11 b/g/n (Draft 3.0)
Chipset	Ralink RT3070
Host Interface	USB 2.0 Backward Compatible (Standard-A Type connector)
Operating Frequency	802.11b/g/n (2412 ~ 2484 MHz)
Dimensions (L x W x H)	15 x 15 x 155 mm(0.59 x 0.59 x 6.10")
WPS Support	Yes
Installation Guide	Wi-Fi USB Adapter

Packing List

1. WiFi USB Adaptor
2. Installation Guide
3. Mini USB to standard USB adapter (For GV-BX1200 Series / 1300 Series / 2400 Series / 3400 Series / 5300 Series only)