

Full HD Flat Dome Camera

DC-F1211

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Fixed-focal lens(f=4.0mm)
- PoE(IEEE 802.3af class 1)
- Supports ONVIF



SPECIFICATIONS

VIDEO																													
Image Sensor	1/2.7" CMOS																												
Max. Resolution	1920 x 1080																												
Scanning Mode	Progressive Scan																												
Lens type	Fixed-focal																												
Focal Length	f=4.0mm																												
Aperture	F=2.0																												
Iris Control	Fixed Iris																												
Angular Field of View	86°(H), 47°(V), 101°(D)																												
Pan/Tilt Range	Pan: -60° ~ 60°, Tilt: 0° ~ 80°, Rotate: -176° ~ 176°																												
Min. Illumination	COLOR : 0.4 lux @ F2.0 B/W : 0.2 lux @ F2.0																												
S/N Ratio	more than 45dB																												
Dynamic Range	more than 70dB																												
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1-1/5,1/7.5,1/15)																												
Day & Night	Electrical																												
IR Distance (LEDs)	-																												
Image Setting	Configurable Exposure, White Balance, Sharpness																												
Digital Noise Reduction	Configurable 2DNR																												
Backlight Compensation	On / Off / HSBLC																												
Image Stabilizer	-																												
Privacy Masking	16 Zones																												
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone																												
Video Out	1 BNC																												
NETWORK																													
	<table border="1"> <thead> <tr> <th>DirectIP Mode</th> <th>Compatibility Mode</th> </tr> </thead> <tbody> <tr> <td>Video Compression</td> <td>H.264(MP), M-JPEG</td> </tr> <tr> <td>Bitrate Control</td> <td>H.264 - CBR / VBR</td> </tr> <tr> <td>Max. Frame Rate</td> <td>30fps : 1920 x 1080</td> </tr> <tr> <td>Audio Compression</td> <td>-</td> </tr> <tr> <td>Two-way audio</td> <td>-</td> </tr> <tr> <td>IP Camera Protocol</td> <td>DirectIP IDIS ONVIF Profile S</td> </tr> <tr> <td>Supported Resolution</td> <td>1920x1080, 1280x720, 704x480, 640x360, 352x240 1920x1080, 1280x720, 704x480, 352x240</td> </tr> <tr> <td>Multi-Video Streaming</td> <td>Quadruple streaming Triple streaming</td> </tr> <tr> <td>Network Protocols</td> <td>Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP Multi-User Authority, IEEE 802.1x</td> </tr> <tr> <td>Security</td> <td>SSL Encryption IP Filtering, HTTPS, SSL Encryption</td> </tr> <tr> <td>Remote Access Client</td> <td>DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite</td> </tr> <tr> <td>Ethernet</td> <td>RJ45(10/100BASE-T)</td> </tr> <tr> <td>Edge Storage</td> <td>-</td> </tr> </tbody> </table>	DirectIP Mode	Compatibility Mode	Video Compression	H.264(MP), M-JPEG	Bitrate Control	H.264 - CBR / VBR	Max. Frame Rate	30fps : 1920 x 1080	Audio Compression	-	Two-way audio	-	IP Camera Protocol	DirectIP IDIS ONVIF Profile S	Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240 1920x1080, 1280x720, 704x480, 352x240	Multi-Video Streaming	Quadruple streaming Triple streaming	Network Protocols	Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP Multi-User Authority, IEEE 802.1x	Security	SSL Encryption IP Filtering, HTTPS, SSL Encryption	Remote Access Client	DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite	Ethernet	RJ45(10/100BASE-T)	Edge Storage	-
DirectIP Mode	Compatibility Mode																												
Video Compression	H.264(MP), M-JPEG																												
Bitrate Control	H.264 - CBR / VBR																												
Max. Frame Rate	30fps : 1920 x 1080																												
Audio Compression	-																												
Two-way audio	-																												
IP Camera Protocol	DirectIP IDIS ONVIF Profile S																												
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240 1920x1080, 1280x720, 704x480, 352x240																												
Multi-Video Streaming	Quadruple streaming Triple streaming																												
Network Protocols	Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP Multi-User Authority, IEEE 802.1x																												
Security	SSL Encryption IP Filtering, HTTPS, SSL Encryption																												
Remote Access Client	DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite																												
Ethernet	RJ45(10/100BASE-T)																												
Edge Storage	-																												
ALARM & EVENT																													
Trigger Event	Motion Detection, Tampering, TripZone																												
Event Buffering (Pre & Post)	yes (up to 60MB)																												
Event Notification	Remote S/W, Email (with Image)																												
Audio In/ Out	-																												
Alarm In/ Out	-																												
ENVIRONMENTAL																													
Vandal-proof Casing	-																												
Out-door Ready	-																												
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)																												
Operating Humidity	0% ~ 90%																												
ELECTRICAL																													
Power Source	PoE(IEEE 802.3af class 1)																												
Power Consumption	3.6W																												
Approvals	FCC, CE(50130-4), KC																												
MECHANICAL																													
Dimensions	95mm x 56.21mm x 120mm (3.75" x 2.22" x 4.73")																												
Weight	0.25 kg (0.56 lb)																												

DIMENSIONS

(Unit - mm)

