

**JVC**

The Perfect Experience

FIXED NETWORK DOME CAMERA

**VN-V225U**

Release Jul. 2009



*Recessed mountable*



- **1/4" Progressive Scan CCD + Built-in 3.8x variable-focal**
- **Motion JPEG and MPEG-4 Full Frame Dual Stream**  
VGA MJPEG and MPEG-4 at 30fps each simultaneously
- **True Day/Night for night time surveillance**
- **Bi-Directional Audio Support**  
Two-way audio communication via mic-in and line-out
- **Free Shape Privacy Masking**
- **Compact enclosure dia. 145mm, 5-3/4 inch**
- **New Fine Focus Adjust mechanism [Patent pending]**
- **PoE / 24 VAC power supply**
- **Great partners about to support – Milestone, Verint, AMX**
- **Supported by JVC VR-N900/1600 and VN-RS800U system**

*Fine Focus Adjust mech.*



## NEW PRODUCT NEWS

### ■ VN-V225U Specifications

Camera and lens	Image device	1/4" Progressive scan CCD, 330,000 pixels (768H x 494 V)
	Lens	3.8x (2.8mm to 10.5 mm) variable focal length
	View angle	73 deg(H) x 54 deg(V) to 20 deg(H) x 15 deg(V)
	Angle adjustment	Pan:350 deg, Tilt:+/-80 deg, Rotation:+/-100 deg
	Minimum Illumination <B&W mode>	0.4 lx, 50%, AGC SUPER <0.03 lx, 50%, AGC SUPER>
	Day/Night	True Day/Night
	White Balance	ATW/AWC
	Electronic Shutter	Auto, 1/30 to 1/10,000, Flickerless
	Sens Up	OFF/ x2 to x62
	BLC	OFF / ON (4 patterns)
	Gamma level	Adjustable
	Privacy Masking	Free Shape and unlimited number of masked area
	Display mode	Custom / LCD1 / LCD2 / CRT
	Motion Detection	Yes
	Network	Alarm Interface
Monitor Output (for setting)		NTSC/PAL selectable. RCA jack, Composite video signal:1.0V(p-p), 75 ohms
Audio		Two-way (full/half duplex) or one way Wires for Mic. IN / Line OUT μ-law 64kbps, AD/DA 16bits Fs=8kHz
Network Interface		RJ45(Category 5) 10Base-T/100Base-TX Auto Negotiation
Network Protocols		TCP/UDP/IP/HTTP/DHCP/SMTP/SNTP/FTP/DSCP/ARP/ICMP/RTP/IGMP/IPv6 JVC API, VSIP, AMX Device Discovery (TBA)
Resolution		640x480, 320x240
Compression and Frame Rate		MJPEG and MPEG-4 30 fps each simultaneously
Data transmission		Unicast / Multicast (IGMP Ver.2)
General	Max. client	20 simultaneous users, Unlimited users by multicast
	Pre-Post Recording	Yes (8MByte RAM)
	Other function	Mail notice, Web server, FTP client, DHCP client, SNTP client, Access protection by 3 level password
	Power	PoE (IEEE802.3af compliant) / 24 VAC 50Hz/60Hz
	Operating Temperature	-10 to 50 deg.C / 14 to 122 deg.F
General	Dimensions	Dia.145mm (5-3/4) x H.120mm (4-3/4)
	Mass	800g (1.8 lbs)
	Built-in Viewer requirement	PC: Windows Vista Business(SP1), Windows XP Pro(SP2)/Home(SP2) Pentium4 2 GHz (WinXP) / 1GB RAM / 512M HDD, IE7 for Vista, IE6 for XP Display and video card: 1024 x 768 True color (24bit or 32bit) VRAM 256MB

Information in this document is subject to change without notice.  
 Copyright 2009 Victor Company of Japan, Limited. All rights reserved.  
 All product names stated in this document are trademarks or registered trademarks of their respective companies.  
 Marks such as TM, ®, and © are omitted in this document.