

APS-412

BACKUP POWER SUPPLY

The switching mode power supply designed to power 12 V devices. It is equipped with a dedicated connector for use with SATEL devices. Its design enables it to be easily installed in the SATEL offered enclosure or on the DIN rail.

- EN50131-6 Grade 2 compliant
- high efficiency 12 V DC switching mode power supply, requiring no mains transformer
- 4 A total output current
- short circuit and overload protection
- designed for use with sealed lead-acid batteries
- optionally selected battery charging current
- battery deep discharge protection
- 3 OC outputs for trouble indication
- optical indication of mains, battery and overload status
- audible trouble signal
- dedicated connector for use with new SATEL modules
- designed for mounting on DIN 35 mm rail and in **OPU-3 P**, **OPU-4 P** and **OPU-4 PW** enclosures



TECHNICAL DATA

Environmental class	II
Power supply type	A
Enclosure dimensions	122 x 59 x 77 mm
Operating temperature range	-10...+55 °C
Supply voltage	230 V AC
Weight	306 g
Battery failure voltage threshold (±10%)	11,5 V
Battery cut-off voltage (±10%)	10,5 V
Rated output voltage	12 V DC
Output current	4 A
Battery charging current (switchable)	0,5 A / 1 A
Current-carrying capacity: WS, WB, WP (OC type) outputs	50 mA

