

Entry-level Dome Camera

MTC-525DH


FEATURES

MTC-525DH



MTC-525DH

- ◆ 1/3" Progressive Scan Sensor
- ◆ Excellent Low Light Performance
- ◆ 550TVL, 0.4Lux@F2.0
- ◆ Built-in DNR
- ◆ **Anti-Color Rolling**
- ◆ Low consumption, 12Vdc, 0.5W



Tol: ±0.5 Unit:mm

SPECIFICATIONS

MTC-525DH	
TV System	PAL NTSC
Image Sensor	1/3" Progressive Scan Sensor
Number of Total Pixels	762(H)x504(V) 762(H)x504(V)
Resolution ; DSP	550TVL
Minimum Illumination	0.4Lux@F2.0
Video Output ; Connector	1.0Vp-p Composite, 75Ω (BNC)
Signal to Noise Ratio (S/N)	More than 48dB (AGC off)
Gamma Correction	0.45
IR LED ; Working Distance	NA
Synchronizing System	INTERNAL
Digital Day&Night Mode	NA
Electronic Shutter	AUTO (1/50(60)~1/100,000 sec)
Automatic Gain Control	AUTO
White Balance	ATW
Back Light Compensation	OFF
Flickerless	NA
Dynamic Noise Reduction	AUTO
Anti-Color Rolling	AUTO
Automatic IRIS ; Connector	NA
Adjustment VR	Built-in Board Lens
Lens, Angle of View(H)	Standard:f3.6mm/F2.0/90°, Options:f2.8mm/F2.0/120°, f6.0mm/F1.8/60°
Water Resistance	NA
Max. Breaking Strength	NA
Power Supply ; Consumption	12Vdc±10% ; 0.5W (41.6mA)
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C
Operation ; Storage Humidity	Maximum:RH80% ; RH90%
Dimensions	85(DIA)x50(H)mm
Net Weight	100g
Accessories Option	NA

*Specifications are unfixd and do not apply to customized projects. 121116

