

# Entry-level IR Dome Camera

Products List &gt; Entry-level IR Dome Camera &gt; MTC-L605DH

## MTC-L605DH

### FEATURES



MTC-L605DH



Option:



MTB-201





Wall Mount

Attach Ceiling  
Top Plate

## MTC-L605DH

- ◆ 1/3" High Sensitivity CCD
- ◆ 600TVL, 0.00Lux (IR LED on at 2 Lux)
- ◆ Built-in 24 IR LEDs
- ◆ Digital WDR
- ◆ Shutter Mode (Auto)
- ◆ Built-in DNR
- ◆ **Smart Intelligent IR Light Control**
- ◆ Double Glass Lens for Avoiding Halos & Blur
- ◆ 12Vdc

DC Jack 12Vdc



Tol:±0.5 Unit:mm

### SPECIFICATIONS

MTC-L605DH	
TV System	PAL
Image Sensor	1/3" High Sensitivity CCD
Number of Total Pixels	795(H)x596(V)
Resolution ; DSP	600TVL
Minimum Illumination	0.3Lux@F2.0
Wide Dynamic Range	Digital WD ; 128x Normal Camera
Video Output ; Connector	1.0Vp-p Composite, 75Ω (BNC)
Signal to Noise Ratio (S/N)	More than 48dB
Gamma Correction	0.45
IR LED ; Working Distance	24 units (IR LEDs on<2Lux) ; Indoor:15~20m
Menu	NA
Title	NA
Synchronizing System	INTERNAL
Digital Day&Night Mode	AUTO
Electronic Shutter	AUTO (1/50(60)~1/100,000 sec)
Automatic Gain Control	AUTO
White Balance	ATW
Back Light Compensation	OFF
Flickerless	OFF
Dynamic Noise Reduction	2D
Language	NA
Motion Detection ; Privacy	NA
Camera Control Interface	NA
Automatic IRIS ; Connector	NA
Lens Mount	Built-in Board Lens
Lens, Angle of View(H)	Standard:f4.3mm/F2.0/63°, Options:f6.0mm/47.5°
Water Resistance	NA
Max. Breaking Strength	NA
Power Supply ; Consumption	12Vdc ; IR on:3.6W IR off:1.0W
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C
Operation ; Storage Humidity	Maximum:RH80% ; RH90%
Dimensions	106(DIA)x95(H)mm
Net Weight	275g
Accessories Option	Wall Bracket:MTB-201